

**“JIFFY”** MASONRY  
**Concrete** FOR THE PROFESSIONAL USER



SHOOK MANUFACTURED PRODUCTS, INC.  
WWW.SHOOKMFG.COM

AKRON, OH  
800.354.9792

**“JIFFY”** MASONRY



# “JIFFY” MASONRY Concrete

FOR THE PROFESSIONAL USER



## Material Application

Attaches wood or metal  
to concrete, brick, cement block or masonry



### **Slotted Indented Hex Washer Head, Hi-Low, Notched Threads, Diamond Point, Blue Ceramic Coating**

Attaches wood or metal  
to concrete, brick, cement block or masonry

Lengths  
1-1/4" - 4"

Blue Ceramic Coating



### **Phillips Flat Head, Hi-Low, Notched Threads, Diamond Point, Blue Ceramic Coating**

Attaches wood or metal  
to concrete, brick, cement block or masonry

Lengths  
1-1/4" - 4"

Blue Ceramic Coating

FOR THE PROFESSIONAL USER attaching wood or metal to concrete, brick and cement block or masonry

- Meets ASTM A 510 for carbon steel manufacturing
- Exceeds 500/hrs. salt spray resistance
- ACQ Compatible
- Notched threads for cutting into concrete, brick and cement block

# “JIFFY” MASONRY

## Slotted Indented Hex Washer Head, Hi-Low, Notched Threads, Diamond Point, Blue Ceramic Coating



- Meets ASTM A 510 for carbon steel manufacturing
- Exceeds 500/hrs. salt spray resistance
- ACQ Compatible
- Notched threads for cutting into concrete, brick and cement block

## Material Application

Attaches wood or metal  
to concrete, brick, cement block or masonry

Size	Fixture Thickness	Driver Size (A.F.) # Head Size	Recommended Drill Bit	Bulk Quantity	Carton Weight*
3/16x1-1/4	0-1/4"	1/4" A.F.	5/32	5,000	41
3/16x1-3/4	1/4"-3/4"	1/4" A.F.	5/32	3,000	32
3/16x2-1/4	3/4"-1-1/4"	1/4" A.F.	5/32	2,500	32
3/16x2-3/4	1-1/4"-1-3/4"	1/4" A.F.	5/32	2,000	32
3/16x3-1/4	1-3/4"-2-1/4"	1/4" A.F.	5/32	1,500	28
3/16x3-3/4	2-1/4"-2-3/4"	1/4" A.F.	5/32	1,000	21
3/16x4	2-1/2"-3"	1/4" A.F. #8 Head	5/32	1,000	23
1/4x1-1/4	0-1/4"	5/16" A.F.	3/16	3,000	36
1/4x1-3/4	1/4"-3/4"	5/16" A.F.	3/16	2,000	33
1/4x2-1/4	3/4"-1-1/4"	5/16" A.F.	3/16	1,500	30

\* Carton weights are approximate and may vary.

## Slotted Indented Hex Washer Head, Hi-Low, Notched Threads, Diamond Point, Blue Ceramic Coating



- Meets ASTM A 510 for carbon steel manufacturing
- Exceeds 500/hrs. salt spray resistance
- ACQ Compatible
- Notched threads for cutting into concrete, brick and cement block

### Material Application

Attaches wood or metal  
to concrete, brick, cement block or masonry

Size	Fixture Thickness	Driver Size (A.F.) # Head Size	Recommended Drill Bit	Bulk Quantity	Carton Weight*	
1/4x2-3/4	1-1/4"-1-3/4"	5/16" A.F.	3/16	1,000	25	
1/4x3-1/4	1-3/4"-2-1/4"	5/16" A.F.	3/16	1,000	29	
1/4x3-3/4	2-1/4"-2-3/4"	5/16" A.F.	3/16	500	17	
1/4x4	2-1/2"-3"	5/16" A.F.	3/16	500	18	

\* Carton weights are approximate and may vary.

## Phillips Flat Head, Hi-Low, Notched Threads, Diamond Point, Blue Ceramic Coating



- Meets ASTM A 510 for carbon steel manufacturing
- Exceeds 500/hrs. salt spray resistance
- ACQ Compatible
- Notched threads for cutting into concrete, brick and cement block

## Material Application

Attaches wood or metal  
to concrete, brick, cement block or masonry

Size	Fixture Thickness	Driver Size (A.F.) # Head Size	Recommended Drill Bit	Bulk Quantity	Carton Weight*	
3/16x1-1/4	0-1/4"	1/4" A.F.	5/32	5,000	35	
3/16x1-3/4	1/4"-3/4"	1/4" A.F.	5/32	3,000	39	
3/16x2-1/4	3/4"-1-1/4"	1/4" A.F.	5/32	2,500	31	
3/16x2-3/4	1-1/4"-1-3/4"	1/4" A.F.	5/32	2,000	29	
3/16x3-1/4	1-3/4"-2-1/4"	1/4" A.F.	5/32	1,500	26	
3/16x3-3/4	2-1/4"-2-3/4"	1/4" A.F.	5/32	1,000	20	
3/16x4	2-1/2"-3"	1/4" A.F. #8 Head	5/32	1,000	22	
1/4x1-1/4	0-1/4"	5/16" A.F.	3/16	3,000	37	
1/4x1-3/4	1/4"-3/4"	5/16" A.F.	3/16	2,000	33	
1/4x2-1/4	3/4"-1-1/4"	5/16" A.F.	3/16	1,500	31	

\* Carton weights are approximate and may vary.

## Phillips Flat Head, Hi-Low, Notched Threads, Diamond Point, Blue Ceramic Coating



- Meets ASTM A 510 for carbon steel manufacturing
- Exceeds 500/hrs. salt spray resistance
- ACQ Compatible
- Notched threads for cutting into concrete, brick and cement block

## Material Application

Attaches wood or metal  
to concrete, brick, cement block or masonry

Size	Fixture Thickness	Driver Size (A.F.) # Head Size	Recommended Drill Bit	Bulk Quantity	Carton Weight*	
1/4x2-3/4	1-1/4"-1-3/4"	5/16" A.F.	3/16	1,000	25	
1/4x3-1/4	1-3/4"-2-1/4"	5/16" A.F.	3/16	1,000	28	
1/4x3-3/4	2-1/4"-2-3/4"	5/16" A.F.	3/16	500	17	
1/4x4	2-1/2"-3"	5/16" A.F.	3/16	500	18	

\* Carton weights are approximate and may vary.