

**“JIFFY”** DRILL  
**Self-Drilling**

FOR THE PROFESSIONAL USER



SHOOK MANUFACTURED PRODUCTS, INC.  
[WWW.SHOOKMFG.COM](http://WWW.SHOOKMFG.COM)

AKRON, OH  
800.354.9792

**“JIFFY”** DRILL

# “JIFFY” DRILL Self-Drilling

FOR THE PROFESSIONAL USER



## Material Application

Attaches metal to metal



### Unslotted Indented Hex Washer Head

Attaches metal to  
metal

Lengths  
1/2" - 3"

Zinc Plated



### Unslotted Indented Hi-Hex Washer Head

Attaches metal  
to metal

Lengths  
3/4"

Zinc Plated



### Unslotted Indented Hex Washer Head w/Bonded Sealing Washer

Attaches metal to  
metal

Lengths  
1/2" - 3"

Zinc Plated

Bonded Sealing Washer Creates Leak Proof Seal



### Unslotted Indented Hex Washer Head, Coated, w/Bonded Sealing Washer

Attaches metal to  
metal

Lengths  
1/2" - 3"

Exceeds 1,000/hr. salt spray resistance  
Bonded Sealing Washer Creates Leak Proof Seal

## FOR THE PROFESSIONAL USER attaching metal to metal

- ICC-ES Evaluation Report: ESR-3528
- Meets ASTM C 1513 for cold-formed steel framing connections
- Meets F.I.P. -1000.7 for torsional strength & drill speed
- Meets SAE J78 for performance & dimensional specifications
- Meets ASTM A 510 for carbon steel manufacturing
- Meets ASTM F1941 for corrosion resistance

# “JIFFY” DRILL

## Unslotted Indented Hex Washer Head, Zinc Plated



- ICC-ES Evaluation Report: ESR-3528
- Meets ASTM C 1513 for cold-formed steel framing connections
- Meets F.I.P.-1000.7 for torsional strength & drill speed
- Meets SAE J78 for performance & dimensional specifications
- Meets ASTM A 510 for carbon steel manufacturing
- Meets ASTM F1941 for corrosion resistance

## Material Application

Attaches metal to metal

Size	Nominal Size Dia.-TPI	Driver Size (A.F.) # Head Size	Basic Diameter (inch)	Drill Capacity (in.)	Bulk Quantity	Carton Weight*
8x1/2	#8-18	¼" A.F. #8 Head	0.164	.035-.100	10,000	35
8x5/8	#8-18	¼" A.F. #8 Head	0.164	.035-.100	10,000	40
8x3/4	#8-18	¼" A.F. #8 Head	0.164	.035-.100	10,000	45
8x1	#8-18	¼" A.F. #8 Head	0.164	.035-.100	8,000	44
8x1-1/4	#8-18	¼" A.F. #8 Head	0.164	.035-.100	5,000	33
8x1-1/2	#8-18	¼" A.F. #8 Head	0.164	.035-.100	5,000	38
8x2	#8-18	¼" A.F. #8 Head	0.164	.035-.100	3,000	29
10x1/2	#10-16	5/16" A.F. #10 Head	0.190	.035-.110	8,000	40
10x5/8	#10-16	5/16" A.F. #10 Head	0.190	.035-.110	8,000	44
10x3/4	#10-16	5/16" A.F. #10 Head	0.190	.035-.176	8,000	50

\* Carton weights are approximate and may vary.

Size	Nominal Size Dia.-TPI	Driver Size (A.F.) # Head Size	Basic Diameter (inch)	Drill Capacity (in.)	Bulk Quantity	Carton Weight*
10x1	#10-16	5/16" A.F. #10 Head	0.190	.035-.176	5,000	40
10x1-1/4	#10-16	5/16" A.F. #10 Head	0.190	.035-.176	4,000	37
10x1-1/2	#10-16	5/16" A.F. #10 Head	0.190	.035-.176	3,000	32
10x2	#10-16	5/16" A.F. #10 Head	0.190	.035-.176	2,000	26
10x2-1/2	#10-16	5/16" A.F. #10 Head	0.190	.035-.176	1,000	15
10x3	#10-16	5/16" A.F. #10 Head	0.190	.035-.176	1,000	18
12x3/4	#12-14	5/16" A.F.	0.216	.035-.210	4,000	33
12x1	#12-14	5/16" A.F.	0.216	.035-.210	4,000	40
12x1-1/4	#12-14	5/16" A.F.	0.216	.035-.210	3,000	35
12x1-1/2	#12-14	5/16" A.F.	0.216	.035-.210	3,000	40
12x2	#12-14	5/16" A.F.	0.216	.035-.210	2,000	33

\* Carton weights are approximate and may vary.

Size	Nominal Size Dia.-TPI	Driver Size (A.F.) # Head Size	Basic Diameter (inch)	Drill Capacity (in.)	Bulk Quantity	Carton Weight*
12x2-1/2	#12-14	5/16" A.F.	0.216	.035-.210	1,500	30
12x3	#12-14	5/16" A.F.	0.216	.035-.210	1,000	23
14x3/4	#14-14	3/8" A.F.	0.250	.060-.220	4,000	50
14x1	#14-14	3/8" A.F.	0.250	.060-.220	3,000	45
14x1-1/4	#14-14	3/8" A.F.	0.250	.060-.220	2,000	35
14x1-1/2	#14-14	3/8" A.F.	0.250	.060-.220	2,000	40
14x2	#14-14	3/8" A.F.	0.250	.060-.220	1,500	38
14x2-1/2	#14-14	3/8" A.F.	0.250	.060-.220	1,000	30
14x3	#14-14	3/8" A.F.	0.250	.060-.220	1,000	35

\* Carton weights are approximate and may vary.

# "JIFFY" DRILL Self-Drilling

FOR THE PROFESSIONAL USER



## Material Application

Attaches metal to metal

### Unslotted Indented Hi-Hex Washer Head, Zinc Plated



- ICC-ES Evaluation Report: ESR-3528
- Meets ASTM C 1513 for cold-formed steel framing connections
- Meets F.I.P.-1000.7 for torsional strength & drill speed
- Meets SAE J78 for performance & dimensional specifications
- Meets ASTM A 510 for carbon steel manufacturing
- Meets ASTM F1941 for corrosion resistance

Size	Nominal Size Dia.-TPI	Driver Size (A.F.) # Head Size	Basic Diameter (inch)	Coating	Bulk Quantity	Carton Weight*
10x3/4	#10-16	5/16" A.F. #10 Hi-Head	0.190	Zinc	6,000	42

### Unslotted Indented Hi-Hex Washer Head w/Serrations, Zinc Plated



10x3/4	#10-16	5/16" A.F. #10 Hi-Head	0.190	Zinc	6,000	42
--------	--------	------------------------	-------	------	-------	----

\* Carton weights are approximate and may vary.

# Unslotted Indented Hex Washer Head, Zinc Plated w/Bonded Sealing Washer



- ICC-ES Evaluation Report: ESR-3528
- Meets ASTM C 1513 for cold-formed steel framing connections
- Meets F.I.P. -1000.7 for torsional strength & drill speed
- Meets SAE J78 for performance & dimensional specifications
- Meets ASTM A 510 for carbon steel manufacturing
- Meets ASTM F1941 for corrosion resistance

## Material Application

Attaches metal to metal

Bonded Sealing Washer Creates Leak Proof Seal

Size	Nominal Size Dia.- TPI	Driver Size (A.F.) # Head Size	Basic Diameter (inch)	Washer	Drill Capacity (in.)	Bulk Quantity	Carton Weight*
8x1/2	#8-18	¼" A.F. #8 Head	0.164	½" O.D.	.035-.100	5,000	28
8x5/8	#8-18	¼" A.F. #8 Head	0.164	½" O.D.	.035-.100	5,000	30
8x3/4	#8-18	¼" A.F. #8 Head	0.164	½" O.D.	.035-.100	5,000	33
8x1	#8-18	¼" A.F. #8 Head	0.164	½" O.D.	.035-.100	4,000	30
8x1-1/4	#8-18	¼" A.F. #8 Head	0.164	½" O.D.	.035-.100	3,000	26
8x1-1/2	#8-18	¼" A.F. #8 Head	0.164	½" O.D.	.035-.100	2,500	24
8x2	#8-18	¼" A.F. #8 Head	0.164	½" O.D.	.035-.100	2,500	29
10x1/2	#10-16	5/16" A.F. #10 Head	0.190	½" O.D.	.035-.110	4,000	30
10x5/8	#10-16	5/16" A.F. #10 Head	0.190	½" O.D.	.035-.110	4,000	32
10x3/4	#10-16	5/16" A.F. #10 Head	0.190	½" O.D.	.035-.176	4,000	35

\* Carton weights are approximate and may vary.

Size	Nominal Size Dia.- TPI	Driver Size (A.F.) # Head Size	Basic Diameter (inch)	Washer	Drill Capacity (in.)	Bulk Quantity	Carton Weight*
10x1	#10-16	5/16" A.F. #10 Head	0.190	½" O.D.	.035-.176	3,000	32
10x1-1/4	#10-16	5/16" A.F. #10 Head	0.190	½" O.D.	.035-.176	2,500	30
10x1-1/2	#10-16	5/16" A.F. #10 Head	0.190	½" O.D.	.035-.176	2,000	26
10x2	#10-16	5/16" A.F. #10 Head	0.190	½" O.D.	.035-.176	1,500	23
10x2-1/2	#10-16	5/16" A.F. #10 Head	0.190	½" O.D.	.035-.176	1,000	18
10x3	#10-16	5/16" A.F. #10 Head	0.190	½" O.D.	.035-.176	1,000	21
12x3/4	#12-14	5/16" A.F.	0.216	9/16" O.D.	.035-.210	3,000	32
12x1	#12-14	5/16" A.F.	0.216	9/16" O.D.	.035-.210	3,000	37
12x1-1/4	#12-14	5/16" A.F.	0.216	9/16" O.D.	.035-.210	2,500	35
12x1-1/2	#12-14	5/16" A.F.	0.216	9/16" O.D.	.035-.210	2,000	31
12x2	#12-14	5/16" A.F.	0.216	9/16"	.035-.210	1,500	29

\* Carton weights are approximate and may vary.



Size	Nominal Size Dia.- TPI	Driver Size (A.F.) # Head Size	Basic Diameter (inch)	Washer	Drill Capacity (in.)	Bulk Quantity	Carton Weight*
12x2-1/2	#12-14	5/16" A.F.	0.216	9/16" O.D.	.035-.210	1,000	22
12x3	#12-14	5/16" A.F.	0.216	9/16" O.D.	.035-.210	1,000	26
14x3/4	#14-14	3/8" A.F.	0.250	5/8" O.D.	.060-.220	3,000	45
14x1	#14-14	3/8" A.F.	0.250	5/8" O.D.	.060-.220	2,500	44
14x1-1/4	#14-14	3/8" A.F.	0.250	5/8" O.D.	.060-.220	2,000	40
14x1-1/2	#14-14	3/8" A.F.	0.250	5/8" O.D.	.060-.220	2,000	45
14x2	#14-14	3/8" A.F.	0.250	5/8" O.D.	.060-.220	1,500	41
14x2-1/2	#14-14	3/8" A.F.	0.250	5/8" O.D.	.060-.220	1,000	33
14x3	#14-14	3/8" A.F.	0.250	5/8" O.D.	.060-.220	1,000	25

\* Carton weights are approximate and may vary.

# "JIFFY" DRILL Self-Drilling

FOR THE PROFESSIONAL USER



**Material Application**  
Attaches metal to metal

## Unslotted Indented Hex Washer Head, Coated



- ICC-ES Evaluation Report: ESR-3528
- Meets ASTM C 1513 for cold-formed steel framing connections
- Meets F.I.P.-1000.7 for torsional strength & drill speed
- Meets SAE J78 for performance & dimensional specifications
- Rust/Acid Rain Protection
- ACQ Compatible
- Exceeds 1,000/hr. salt spray resistance

Size	Nominal Size Dia.- TPI	Driver Size (A.F.) # Head Size	Basic Diameter (inch)	Washer	Drill Capacity (in.)	Bulk Quantity	Carton Weight*
10x3/4	#10-16	5/16" A.F. #10 Head	0.190	1/2" O.D.	.035-.176	4,000	35
10x1	#10-16	5/16" A.F. #10 Head	0.190	1/2" O.D.	.035-.176	3,000	32
10x1-1/2	#10-16	5/16" A.F. #10 Head	0.190	1/2" O.D.	.035-.176	2,000	26
10x2	#10-16	5/16" A.F. #10 Head	0.190	1/2" O.D.	.035-.176	1,500	23

\* Carton weights are approximate and may vary.

Size	Nominal Size Dia.- TPI	Driver Size (A.F.) # Head Size	Basic Diameter (inch)	Washer	Drill Capacity (in.)	Bulk Quantity	Carton Weight*
12x3/4	#12-14	5/16" A.F.	0.216	9/16" O.D.	.035-.210	3,000	32
12x1	#12-14	5/16" A.F.	0.216	9/16" O.D.	.035-.210	3,000	37
12x1-1/4	#12-14	5/16" A.F.	0.216	9/16" O.D.	.035-.210	2,500	35
12x1-1/2	#12-14	5/16" A.F.	0.216	9/16" O.D.	.035-.210	2,000	31
12x2	#12-14	5/16" A.F.	0.216	9/16"	.035-.210	1,500	29
12x3	#12-14	5/16" A.F.	0.216	9/16" O.D.	.035-.210	1,000	26
14x3/4	#14-14	3/8" A.F.	0.250	5/8" O.D.	.060-.220	3,000	45
14x1	#14-14	3/8" A.F.	0.250	5/8" O.D.	.060-.220	2,500	44
14x1-1/4	#14-14	3/8" A.F.	0.250	5/8" O.D.	.060-.220	2,000	40
14x1-1/2	#14-14	3/8" A.F.	0.250	5/8" O.D.	.060-.220	2,000	45
14x2	#14-14	3/8" A.F.	0.250	5/8" O.D.	.060-.220	1,500	41
14x2-1/2	#14-14	3/8" A.F.	0.250	5/8" O.D.	.060-.220	1,000	33
14x3	#14-14	3/8" A.F.	0.250	5/8" O.D.	.060-.220	1,000	25

\* Carton weights are approximate and may vary.