

**“JIFFY”** DRILL  
**Stainless** FOR THE PROFESSIONAL USER



SHOOK MANUFACTURED PRODUCTS, INC.  
[WWW.SHOOKMFG.COM](http://WWW.SHOOKMFG.COM)

AKRON, OH  
800.354.9792

**“JIFFY”** DRILL



# “JIFFY” DRILL Stainless

FOR THE PROFESSIONAL USER



## Material Application

Attaches metal or aluminum  
to metal or aluminum



### 410 Stainless Steel Unslotted Indented Hex Washer Head

Attaches metal or aluminum  
to metal or aluminum

Lengths

1/2" - 3"



### 410 Stainless Steel Unslotted Indented Hex Washer Head w/Bonded Sealing Washer

Attaches metal or aluminum  
to metal or aluminum

Lengths

1/2" - 3"

Bonded Sealing Washer Creates Leak Proof Seal

FOR THE PROFESSIONAL USER attaching metal to metal

- Meets F.I.P.-1000.7 for torsional strength & drill speed
- Meets SAE J78 for performance & dimensional specifications

# “JIFFY” DRILL

## 410 Stainless Steel Unslotted Indented Hex Washer Head, Self Drilling



- Meets F.I.P.-1000.7 for torsional strength & drill speed
- Meets SAE J78 for performance & dimensional specifications

### Material Application

Attaches metal or aluminum  
to metal or aluminum

Size	Nominal Size Dia.-TPI	Driver Size (A.F.) # Head Size	Basic Diameter (inch)	Drill Capacity (in.)	Bulk Quantity	Carton Weight*
8x1/2	#8-18	¼" A.F. #8 Head	0.164	.035-.100	5,000	18
8x3/4	#8-18	¼" A.F. #8 Head	0.164	.035-.100	5,000	23
8x1	#8-18	¼" A.F. #8 Head	0.164	.035-.100	4,000	22
10x1/2	#10-16	5/16" A.F. #10 Head	0.190	.035-.110	5,000	26
10x3/4	#10-16	5/16" A.F. #10 Head	0.190	.035-.176	4,000	25
10x1	#10-16	5/16" A.F. #10 Head	0.190	.035-.176	3,000	24
10x1-1/4	#10-16	5/16" A.F. #10 Head	0.190	.035-.176	2,500	23
10x1-1/2	#12-14	5/16" A.F. #10 Head	0.190	.035-.176	2,000	21
10x2	#12-14	5/16" A.F. #10 Head	0.190	.035-.176	1,500	15
12x3/4	#12-14	5/16" A.F.	0.216	.035-.210	4,000	33

\* Carton weights are approximate and may vary.

Size	Nominal Size Dia.-TPI	Driver Size (A.F.) # Head Size	Basic Diameter (inch)	Drill Capacity (in.)	Bulk Quantity	Carton Weight*
12x1	#12-14	5/16" A.F.	0.216	.035-.210	3,000	30
12x1-1/4	#12-14	5/16" A.F.	0.216	.035-.210	3,000	35
12x1-1/2	#12-14	5/16" A.F.	0.216	.035-.210	2,500	33
12x2	#12-14	5/16" A.F.	0.216	.035-.210	2,000	33
14x3/4	#14-14	3/8" A.F.	0.250	.035-.220	3,000	38
14x1	#14-14	3/8" A.F.	0.250	.035-.220	3,000	30
14x1-1/4	#14-14	3/8" A.F.	0.250	.035-.220	3,000	35
14x1-1/2	#14-14	3/8" A.F.	0.250	.035-.220	1,500	30
14x2	#14-14	3/8" A.F.	0.250	.035-.220	1,000	25
14x2-1/2	#12-14	3/8" A.F.	0.250	.035-.220	800	24
14x3	#14-14	3/8" A.F.	0.250	.035-.220	500	17

\* Carton weights are approximate and may vary.

# 410 Stainless Steel Unslotted Indented Hex Washer Head, w/Bonded Sealing Washer, Self Drilling



- Meets F.I.P.-1000.7 for torsional strength & drill speed
- Meets SAE J78 for performance & dimensional specifications

## Material Application

Attaches metal or aluminum  
to metal or aluminum

Bonded Sealing Washer Creates Leak Proof Seal

Size	Nominal Size Dia.- TPI	Driver Size (A.F.) # Head Size	Basic Diameter (inch)	Washer	Drill Capacity (in.)	Bulk Quantity	Carton Weight*
8x1/2	#8-18	¼" A.F. #8 Head	0.164	½" O.D.	.035-.100	5,000	32
8x3/4	#8-18	¼" A.F. #8 Head	0.164	½" O.D.	.035-.100	5,000	35
8x1	#8-18	¼" A.F. #8 Head	0.164	½" O.D.	.035-.100	4,000	30
10x3/4	#10-16	5/16" A.F. #10 Head	0.190	½" O.D.	.035-.176	4,000	35
10x1	#10-16	5/16" A.F. #10 Head	0.190	½" O.D.	.035-.176	3,000	31
10x1-1/4	#10-16	5/16" A.F. #10 Head	0.190	½" O.D.	.035-.176	2,500	30
10x1-1/2	#10-16	5/16" A.F. #10 Head	0.190	½" O.D.	.035-.176	2,000	26
10x2	#10-16	5/16" A.F. #10 Head	0.190	½" O.D.	.035-.176	1,500	22
12x3/4	#12-14	5/16" A.F.	0.216	9/16" O.D.	.035-.210	3,000	32
12x1	#12-14	5/16" A.F.	0.216	9/16" O.D.	.035-.210	3,000	37

\* Carton weights are approximate and may vary.

Size	Nominal Size Dia.- TPI	Driver Size (A.F.) # Head Size	Basic Diameter (inch)	Washer	Drill Capacity (in.)	Bulk Quantity	Carton Weight*
12x1-1/4	#12-14	5/16" A.F.	0.216	9/16" O.D.	.035-.210	2,500	35
12x1-1/2	#12-14	5/16" A.F.	0.216	9/16" O.D.	.035-.210	2,500	39
12x2	#12-14	5/16" A.F.	0.216	9/16" O.D.	.035-.210	1,500	28
14x3/4	#14-14	3/8" A.F.	0.250	5/8" O.D.	.035-.220	3,000	45
14x1	#14-14	3/8" A.F.	0.250	5/8" O.D.	.035-.220	2,500	44
14x1-1/4	#14-14	3/8" A.F.	0.250	5/8" O.D.	.035-.220	2,000	40
14x1-1/2	#14-14	3/8" A.F.	0.250	5/8" O.D.	.035-.220	1,500	34
14x2	#14-14	3/8" A.F.	0.250	5/8" O.D.	.035-.220	1,000	28
14x2-1/2	#14-14	3/8" A.F.	0.250	5/8" O.D.	.035-.220	800	26
14x3	#14-14	3/8" A.F.	0.250	5/8" O.D.	.035-.220	500	18

\* Carton weights are approximate and may vary.